

423 AG Impact Sprinkler



A metal impact sprinkler, specifically designed for irrigation of field edges

423 AG Impact Sprinkler

- High water distribution with spacing up to 14 m
- Durable, heavy-duty construction
- Sand and dust protection sleeve ensures reliable operation and durability
- WP - Hammer ensures all water inside the irrigation pattern and prevents irrigating roads and neighbors.

423 AG - Full and part circle metal impact sprinkler 1/2", specifically designed for irrigation of fields edges.

Applications:
Nurseries, agricultural fields edge, residential and small public area.

Technical Data

Recommended working pressure	2.0 - 4.0 bar
Pressure (for flow rate calculation)	3.0 bar
Trajectory Angle	23° - 25°
Wetted diameter	23 - 28 m
Connections Type	1/2" Male



423 AG

423 AG - Performance table

Nozzle Color & Size	Pressure	Flow Rate	Wetted Diameter	Min. Qty.	
mm	bar	m³/h	m	units	SKU
Green 3.2	2.0	0.570	23	50	101094254
	3.0	0.700	25		
	4.0	0.810	26		
Blue 3.5	2.0	0.660	24	50	101094255
	3.0	0.810	26		
	4.0	0.930	27		
Black 4.0*	2.0	0.850	25	50	101094256
	3.0	1.030	27		
	4.0	1.180	28		

* Standard nozzle
Performance table prepared under laboratory conditions
For windy conditions use closer spacing



Case study outcomes are for information purposes only and actual results may vary. This literature has been compiled for worldwide circulation and the descriptions, photos, and information are for general purpose use only. Please consult with an irrigation specialist and technical specifications for proper use of Rivulis products. Because some products are not available in all regions, please contact your local dealer for details. Rivulis reserves the right to change specifications and the design of all products without notice. Every effort has been used to ensure that product information, including data sheets, schematics, manuals and brochures are correct. However information should be verified before making any decisions based on this information.